




NABRICO



DF-156 Hydra-Electric Winch

Features & Specifications

- Self-contained hydraulic / electric power unit with Stainless Steel tank.
- Winch operation can also be achieved by customer supplied hydraulic power or remote mounted power supply.
- Fail safe brake.
- Mechanical dog for emergency manual operation.
- Hot-dipped galvanized standard.
- Hydraulic system prevents power spikes.
- Free wheeling feature to allow faster cable pull-out.
- Stainless Steel components: control box, guards, tanks, and fasteners.
- Fully Synthetic Biodegradable Hydraulic fluid.
- True left or right hand models for use in pairs.

MODEL	HOLDING DOG & OR BRAKE	LINE PULL @ FIRST LAYER			DRUM CAPACITIES (FT.)				LINE SPEED	WEIGHT	DIMENSIONAL DATA		
		HYDRA ELECTRIC RATED	HYDRA ELECTRIC MAX	HANDWHEEL ONE MAN	5/8	3/4	7/8	1			FPM	LBS	W
DF-156-10-6-HE	10 TONS	2272 AT 830 PSI	3150 AT 1119 PSI	7,000 LBS	174	129	-	-	23.5	897	11"	22"	47"
DF-156-20-7-HE	20 TONS	9382 AT 1138 PSI	11700 AT 1381 PSI	14,000 LBS	109	57	39	21	17.2	1284	16"	30"	41"
DF-156-40-11-HE	40 TONS	17213 AT 1695 PSI	18000 AT 1797 PSI	15,000 LBS	287	176	130	84	12.8	1930	22"	36"	40"
DF-156-60-11-HE	60 TONS	31771 AT 1998 PSI	33480 AT 2105 PSI	24,000 LBS	572	325	262	200	9.9	3225	24"	47"	51"