



NABRICO



DF-1 Electric Winch Features & Specifications

- Salt water package standard on all power winches.
- Hot-dipped galvanized.
- Stainless or silicon bronze fasteners.
- 3-ply conveyer belt covers (damage and corrosion-resistant).
- 3-tooth locking dog with large release and fail-safe disc brake.
- Provisions for emergency manual operation with cordless drill.
- NEMA motor design with cycloidal gearbox.
- Control box option: NEMA 4X stainless steel.
- Minimal maintenance and easy to repair.
- Variable frequency drive option available. Amp draw limits, variable speeds, and motor protection.
- Made as one model adjustable to true right or left hand models for use in pairs.
- Over 100 fewer parts than other electric winches (no chain or sprockets).
- Heaviest winch in its class.
- 30 Ton - 5 HP motor standard.
- 40 Ton - 7.5 HP motor standard.
- 50 Ton - 10 HP motor standard.
- 65 Ton - 10 HP motor standard.
- Other line pulls and speeds available.

MODEL	HOLDING DOG & OR BRAKE	LINE PULL		LINE SPEED 1ST LAYER FPM	DRUM CAPACITIES (FT.)					WEIGHT LBS.	DIMENSIONAL DATA		
		@ RATED AMPS-LBS	@ MOTOR STALL		1/2	5/8	3/4	7/8	1		W	L	H
DF-1-30	30 TONS	12500	18750	14	361	228	138	120	66	1700	20"	22"	55"
DF-1-40	40 TONS	15600	23400	16	-	287	180	130	100	1850	21"	24"	67"
DF-1-50	50 TONS	20800	31200	16	-	287	180	130	100	1850	21"	24"	69"
DF-1-65	65 TONS	37800	56700	9	-	572	325	262	200	3200	24"	30"	79"